

Aria Line

Características / Characteristics

Luminaria LED fabricada en perfil de aluminio de alta calidad.

LED fixture made in high quality extruded aluminum.


Temperatura de color 4000K y 6500K.

Color temperature 4000K and 6500K.


Disponible con batería de emergencia remota.

Available with remote backup battery.


Curva Fotométrica / Photometric Curve



Sistema de unión
Union system
(opcional)
P04857-36



Dimensiones Generales / General Dimensions



Dimensión Nominal	A (mm)	B (mm)	C (mm)
24"	600	81	84
48"	1180	81	84
96"	2360	81	84

Modelo Model	Dimensión Nominal Nominal Dimension	Potencia Power	Flujo Luminoso Luminous flux	Difusor Diffuser	Instalación Installation	Temp. de color Color temp.	Eficacia Efficacy	Base Base	Código con batería Code with battery	
ARIA LINE	24"	20 W	2000 lm			4000 K	>100	P07032-36		
	24"	20 W	2000 lm			6500 K	>100	P04336-23		
	48"	20 W	2000 lm			4000 K	>100	P07029-36	P07620-36	
	48"	20 W	2000 lm			6500 K	>100	P08530-36	P08529-36	
	48"	25 W	3000 lm			4000 K	>120	P06734-36	P06521-36	
	48"	25 W	3000 lm			6500 K	>120	P08532-36	P08531-36	
	48"	35 W	4000 lm		D15	Colgar	4000 K	>120	P06441-36	P08261-36
	48"	35 W	4000 lm				6500 K	>120	P04337-23	P04370-23
	96"	35 W	4000 lm				4000 K	>120	P08432-36	P08533-36
	96"	35 W	4000 lm				6500 K	>120	P07961-36	P08534-36
	96"	50 W	6000 lm				4000 K	>120	P04564-36	P07699-23
	96"	50 W	6000 lm				6500 K	>120	P06920-23	P08535-36
	96"	70 W	8000 lm				4000 K	>120	P06920-23	P07128-23
	96"	70 W	8000 lm				6500 K	>120	P06706-23	P08536-36

Los valores indicados de flujo luminoso y potencia son nominales, y tienen una tolerancia de $\pm 10\%$.

