

Aria Line

Características / Characteristics

Luminaria LED fabricada en perfil de aluminio de alta calidad.

LED fixture made in high quality extruded aluminum.

Temperatura de color 4000K y 6500K.

Color teemperature 4000K and 6500K.


Disponible con batería de emergencia remota.

Available with remote backup battery.




Dimensiones Generales / General Dimensions

Dimensión Nominal	A (mm)	B (mm)	C (mm)
23"	602	81	84
46"	1192	81	84
69"	1766	81	84
92"	2355	81	84



Curva Fotométrica / Photometric Curve



CO / C180 C90 / C270
cd / 1000 lm

ARIA LINE SMD 4000 lm 48"

Modelo Model	Dimensión Nominal Dimension	Potencia Power	Flujo Luminoso Luminous flux	Difusor Diffuser	Instalación Installation	Temp. de color Color Temp.	Eficacia Efficacy	Código Code	Código con batería Code with battery
ARIA LINE	23"	20 W	2000 lm	D 15	Colgar	4000 K	>100	P07032-36	
	23"	20 W	2000 lm	D 15		6500 K	>100	P04336-36	
	46"	20 W	2000 lm	D 15		4000 K	>100	P07029-36	P07620-36
	46"	20 W	2000 lm	D 15		6500 K	>100	P08530-36	P08529-36
	46"	30 W	3000 lm	D 15		4000 K	>100	P06734-36	P06521-36
	46"	30 W	3000 lm	D 15		6500 K	>100	P08532-36	P08531-36
	46"	40 W	4000 lm	D 15		4000 K	>100	P06441-36	P08261-36
	46"	40 W	4000 lm	D 15		6500 K	>100	P04337-36	P04370-23
	46"	40 W	4000 lm	D 15		4000 K	>100	P08432-36	P08533-36
	92"	40 W	4000 lm	D 15		6500 K	>100	P07961-36	P08534-36
	92"	60 W	6000 lm	D 15		4000 K	>120	P04564-36	P07699-23
	92"	60 W	6000 lm	D 15		6500 K	>120	P04339-23	P08535-36
	92"	80 W	8000 lm	D 15		4000 K	>100	P06920-23	P07128-23
	92"	80 W	8000 lm	D 15		6500 K	>100	P06706-23	P08536-36

Los valores indicados de flujo luminoso y potencia son nominales, y tienen una tolerancia de $\pm 10\%$.

